

REMARKS

Applicants respectfully request that the foregoing amendments be entered prior to examination. An early and favorable action on the merits is respectfully requested.

Respectfully submitted,

Date December 14, 2005

By 

FOLEY & LARDNER LLP
Customer Number: 22428
Telephone: (202) 672-5414
Facsimile: (202) 672-5399

Richard L. Schwaab
Attorney for Applicant
Registration No. 25,479

IAP20 Rec'd PCT/PTO 14 DEC 2005

3-DIMENSIONAL ULTRASONOGRAPHIC DEVICE

Technical Field

[0001] The present invention relates to a three-dimensional
5 ultrasonographic device that three dimensionally (3D) visualizes
a defect, a void, a foreign substance such as an oxide film, and
a peeling state of a joint portion in a structure to be inspected,
by using ultrasonic waves transmitted/received by a large number
of two-dimensionally arranged piezoelectric vibrators.

10

Background Art

[0002] There has been proposed an ultrasonic inspection device
using an ultrasonic transducer composed of a plurality of
piezoelectric vibrators that are formed independently from each other
15 and arranged in a matrix (see, for example, Patent document 1). With
the conventional ultrasonic inspection device, a layer structure
having a plurality of different acoustic characteristics, and a defect,
a ~~void~~ void, and peeling in an inspection object having a curved
surface can be visualized by using ultrasonic waves, but since
20 judgment on the result imaged by the ultrasonic waves relies on eyes,
it is difficult to automatically judge the result and to recognize
the positional relation with the inspection object.

[0003] Such a conventional ultrasonic inspection device has the
following problems.

25 [1] Objective and ~~weight~~ quantitative inspection is difficult since
internal inspection relies on a person's observation of the imaged

result.

[2] Brightness of an image varies at different depths of the inspection object due to the influence of a surface-reflected wave in the inspection object, the attenuation of the ultrasonic wave in the inspection object, and the like.

[3] Continuous imaging of a wide area is not possible due to the limited size of the ultrasonic transducer.

[4] If the periphery of an inspection area of the inspection object is uneven, the ultrasonic wave reflected on the uneven portion of the periphery deteriorates image quality of an internal image of the inspection object.

[5] It is not possible to automatically determine whether abnormality exists or not, based on position and shape information of the defect obtained from the three-dimensional imaging of the interior of the inspection object.

[Patent document 1] Japanese Patent Laid-open Application No. 2003-149213

Disclosure of the Invention

[0004] The present invention was made in order to solve the above-described problems and its object is to provide a three-dimensional ultrasonographic device that achieves improved accuracy of internal inspection using an ultrasonic wave, a wider inspection area, and automatic judgment of the inspection.

[0005] A three-dimensional ultrasonographic device of the present invention includes: an ultrasonic transducer composed of a plurality

of piezoelectric vibrators; a vibrator selecting part which causes an arbitrary one of the plural piezoelectric vibrators to generate an ultrasonic wave; a signal detecting circuit which selectively detects electrical signals that the plural piezoelectric vibrators
5 generate when ~~receiving echoes of the ultrasonic wave,~~ the piezoelectric vibrators receive echoes of the ultrasonic wave, which is generated by the piezoelectric vibrator selected by the vibrator selecting part to ~~be reflected on an inspection object via an acoustic medium~~ pass through an acoustic medium and to be reflected in an
10 inspection object; a signal processing part which generates three-dimensional image data by aperture synthesizing from the electrical signals detected by the signal detecting circuit, in correspondence to meshes in a three-dimensional imaging area set in the inspection object; and a display processing part which has:
15 a function of changing brightness or transparency ~~of~~ with which respective meshes set in the three-dimensional area, according to values of the three-dimensional imaging data generated by the signal processing part; and a function of applying masking or image brightness correction to an image of an unnecessary portion of the
20 three-dimensional imaging data, by multiplying the value of the three-dimensional imaging data by a value set according to a three-dimensional coordinate position (X, Y, Z).

[0006] The present invention can provide a three-dimensional ultrasonographic device that achieves improved accuracy of internal
25 inspection using an ultrasonic wave, a wider inspection area, and automatic judgment of the inspection.

Brief Description of Drawings

[0007] Fig. 1 is a diagram showing a whole configuration of a three-dimensional ultrasonographic device of one embodiment according to the present invention.

[0008] Fig. 2A is a view showing the result of three-dimensional imaging of ~~imaging data~~ an inspection object.

[0009] Fig. 2B is a chart showing the distribution of reflection intensity of a surface-reflected wave in a 3D imaging area.

[0010] Fig. 2C is a view showing an X-Y two-dimensional image of the imaging data.

[0011] Fig. 3A is a view showing the result of three-dimensional imaging of a defective portion (abnormal portion).

[0012] Fig. 3B is a view showing an X-Y two-dimensional image of the defective portion (abnormal portion).

[0013] Fig. 3C is a chart showing a characteristic of the imaging data.

[0014] Fig. 4A is a view showing the result of three-dimensional imaging of a defective portion (abnormal portion).

[0015] Fig. 4B is a view showing an X-Y two-dimensional image of the defective portion (abnormal portion).

[0016] Fig. 4C is a view showing abnormality judgment based on the two-dimensional images.

[0017] Fig. 5A is a view showing the result of three-dimensional imaging of a defective portion (abnormal portion).

[0018] Fig. 5B is a view showing abnormality judgment directly

based on the result of the three-dimensional imaging.

[0019] Fig. 6 is a view showing a driving part used for image connection processing.

[0020] Fig. 7 is a view showing a display screen displaying the
5 result of the image connection processing.

[0021] Fig. 8 is a view showing a structural example where a masking part is disposed for image quality improvement.

Best Mode for Carrying out the Invention

10 [0022] A three-dimensional ultrasonographic device of this embodiment includes: a signal processing part which generates three-dimensional imaging data corresponding to meshes in a three-dimensional imaging area set in an inspection object; and a display processing part which has: a function of changing brightness
15 or transparency ~~of~~ with which respective meshes set in the three-dimensional area, according to values of the three-dimensional imaging data generated by the signal processing part, ~~that the~~
~~respective meshes have for the three-dimensional imaging data;~~ and a function of applying masking or image brightness correction to
20 an image of an unnecessary portion of the three-dimensional imaging data, by multiplying the value of the three-dimensional imaging data by a value set according to a three-dimensional coordinate position (X, Y, Z).

[0023] The display processing part includes a two-dimensional
25 image generating part which sees through the three-dimensional imaging data from totally three directions, namely, a direction from

a front face as viewed from an ultrasonic transducer, and directions vertical to two side faces ~~straight~~ perpendicular to the front face, and projects, on a two-dimensional plane, data with the largest value out of imaging data stacked in each of the see-through directions out of the three-dimensional imaging data to thereby generate three two-dimensional images in the respective directions.

[0024] The three-dimensional ultrasonographic device further includes an outline drawing part which draws an outline of a shape of the inspection object so as to overlay the outline on the three two-dimensional images generated by the two-dimensional image generating part.

[0025] The three-dimensional ultrasonographic device further includes an outline drawing part which draws three-dimensional shapes of an outline of the inspection object and a post-processed portion, by overlaying the three-dimensional imaging data generated by the signal processing part on the three-dimensional imaging area.

[0026] The three-dimensional ultrasonographic device further includes an abnormality judging part which compares the values of the three-dimensional imaging data corresponding to the meshes in the three-dimensional imaging area with a predetermined set value to output the mesh whose value is equal to or larger than the set value, and automatically calculates a ratio of the number of the outputted meshes whose values are equal to or larger than the set value to judge that abnormality exists when an automatically calculated value becomes equal to or larger than a prescribed value.

[0027] The three-dimensional ultrasonographic device includes an

abnormality ~~judging~~ judging/displaying part which compares values of the two-dimensional image data generated by the two-dimensional image generating part with a predetermined set value to output the mesh whose value is equal to or larger than the set value, and compares
5 three-dimensional coordinates of the outputted imaging mesh with preset three-dimensional shape information on an outline shape of the inspection object or on a post-processed portion, thereby detecting whether or not an interference between a defect position and the post-processed portion exists in the inspection object to
10 display a result of the detection.

[0028] The three-dimensional ultrasonographic device further includes an abnormality judging/displaying part which, when the imaging mesh whose value exceeds the predetermined set value is selected from the two-dimensional image data generated by the
15 two-dimensional image generating part, automatically calculates an area of an abnormal portion based on an adjacency state of the selected imaging mesh and judges whether or not the automatically calculated area of the abnormal portion is equal to or larger than a prescribed value to display a result of the judgment.

[0029] The three-dimensional ultrasonographic device includes an abnormality judging/displaying part which compares the values of the three-dimensional imaging data corresponding to the meshes in the three-dimensional imaging area with a predetermined set value to output the mesh whose value is equal to or larger than the set
20 value, and compares three-dimensional coordinates of the outputted mesh with preset three-dimensional shape information on an outline
25

shape of the inspection object and on a post-processed portion, thereby detecting whether or not an interference between a defect position and the post-processed portion exists in the inspection object to display a result of the detection.

5 **[0030]** The three-dimensional ultrasonographic device includes a unit which, when the abnormality judging/displaying part outputs the mesh whose value is equal to or larger than the set value from the three-dimensional imaging data, automatically calculates a volume of the abnormal portion based on an adjacency state of the
10 outputted imaging data and judges whether or not an area of the abnormal portion is equal to or larger than a prescribed value to display a result of the judgment.

[0031] The three-dimensional ultrasonographic device includes:
a mechanism part which mechanically drives the transducer and detects
15 a movement position of the transducer; an image connecting part connecting the plural imaging data that are detected each time the transducer is moved by the mechanism part; and a display part displaying images connected by the image connecting part.

[0032] In this three-dimensional ultrasonographic device, the
20 ultrasonic wave is generated by an arbitrary one of the plural piezoelectric vibrators of the ultrasonic transducer. The signal detecting circuit selectively detects electrical signals that the plural piezoelectric vibrators generate ~~when receiving echoes of the ultrasonic wave,~~ when the piezoelectric vibrators receive echoes
25 of the ultrasonic wave, which is generated by the piezoelectric vibrator to pass through an acoustic medium made of solid or liquid

and to be reflected ~~on~~ in an inspection object made of a layer with a planar or curved boundary and with a single acoustic characteristic or a plurality of acoustic characteristic ~~characteristics~~, ~~via an acoustic medium made of solid or liquid.~~

5 [0033] Then, the signal processing part generates the three-dimensional imaging data by aperture synthesizing from the electrical signal detected by the signal detecting circuit, in correspondence to the meshes in the three-dimensional imaging area set in the inspection object and outputs the three-dimensional imaging data to the display processing part.

[0034] The display processing part changes brightness or transparency ~~of~~ with which respective meshes set in the three-dimensional area, according to values of the three-dimensional imaging data generated by the signal processing part, ~~that the~~
15 ~~respective meshes have for the three-dimensional imaging data.~~

[0035] Further, the display processing part applies masking or image brightness correction to the image of the unnecessary portion of each of the three-dimensional imaging data by multiplying the value of the three-dimensional imaging data by the value set according to the three-dimensional coordinate position (X, Y, Z).

[0036] Thus, the three-dimensional imaging data synthesized in the three-dimensional ultrasonographic device having the ultrasonic transducer and the display images are processed, and the plural imaging data obtained while the ultrasonic transducer is moved are
25 connected according to the position of the ultrasonic transducer, so that it is possible to image a defective portion of the inspection

object for more quantitative and intuitive judgment. Further, in imaging, an area other than the inspection area of the inspection object is masked, so that image quality can be improved.

[0037] The three-dimensional coordinates of the imaging mesh whose value exceeds the set value out of the three-dimensional imaging data generated by the three-dimensional ultrasonographic device or out of the two-dimensional image data generated by the two-dimensional image generating part are compared with the three-dimensional shape information on the outline shape of the inspection object and on the post-processed portion, and based on the comparison, it is judged whether or not the defective portion interferes with the post-processed portion, and the area of the abnormal portion is automatically calculated based on whether or not the adjacency of the imaging mesh exists, so that the automatic judgment of the inspection is enabled.

[0038] Further, the plural imaging data obtained by providing the mechanism part which is capable of moving the ultrasonic transducer while detecting the position thereof are connected according to the position of the ultrasonic transducer, so that a wide area can be imaged.

[0039] Further, a masking part having an aperture at a position corresponding to the inspection area of the surface of the inspection object is provided on the surface of the inspection object, so that it is possible to prevent image quality of the internal image from deteriorating due to the ultrasonic wave reflected on the uneven portion of the periphery of the inspection area.

[0040] Hereinafter, an embodiment of the present invention will be described with reference to the drawings.

[0041] Fig. 1 is a diagram showing a configuration of a three-dimensional ultrasonographic device of one embodiment according to the present invention.

[0042] As shown in Fig. 1, the three-dimensional ultrasonographic device has: a signal generating part 1; a driven element selecting part 2; a matrix sensor 9 as an ultrasonic transducer; a signal detecting circuit 4; a signal processing part 8 which is a central processor and is composed of amplifiers 5a, 5b to 5i, A/D converters 6a, 6b to 6i, and a parallel processor 7; a display processing device 10; and so on. On a ~~front~~ surface of the matrix sensor 9, an acoustic propagation medium 16 is closely attached. The matrix sensor 9 receives an ultrasonic wave U reflected from a defect 14 in an inspection object (object to be irradiated with the ultrasonic wave) 17 via the acoustic propagation medium 16 and a couplant 18. Incidentally, if the acoustic propagation medium 16 is liquid such as, for example, water, the couplant 18 is not necessary.

[0043] The matrix sensor 9 is composed of a plurality of piezoelectric vibrators 21a, 22a, 23a to 29a, 30a, 30b to 30h each made of a piezoelectric element, which are arranged in a matrix, and the driven element selecting part 2 selects and determines one to be driven out of the piezoelectric vibrators 21a and so on, and a driving signal from the signal generating part 1 is led thereto via an electrical lead. Further, electrical signals generated by the piezoelectric vibrators 21a and so on are led to the signal

detecting circuit 4 via electrical leads. When any of the piezoelectric vibrators 21a and so on is electrically driven, an ultrasonic wave is generated owing to its property as a piezoelectric substance, and the generated ultrasonic wave reaches the defect 14 in the inspection object 17 via the acoustic propagation medium 16. Ultrasonic echoes U reflected on the defect 14 are inputted to the piezoelectric vibrators 21a and so on again via the acoustic propagation medium 16, so that the piezoelectric vibrators 21a and so on generate the electrical signals.

[0044] The signal generating part 1 generates a pulsed or continuous driving signal so as to cause the piezoelectric vibrators 21a and so on to generate the ultrasonic waves. The generated driving signal is inputted to the driven element selecting part 2 serving as a vibrator selecting part. The driven element selecting part 2 selects one or plural ones to be driven out of the piezoelectric vibrators 21a and so on and inputs the driving signal led from the signal generating part 1 to the selected one/ones of the piezoelectric vibrators 21a and so on to cause the selected one/ones of the piezoelectric vibrators 21a to generate the ultrasonic wave U.

[0045] The signal detecting circuit 4 is connected to the plural piezoelectric vibrators 21a and so on and detects the electrical signals generated by the piezoelectric ~~vibrator~~ vibrators 21a and so on. The plural ones necessary for inspection out of the detected electrical signals are led to the amplifiers 5a, 5b to 5i in the signal processing part 8 respectively. The signal detecting circuit selectively detects electrical signals that the plural piezoelectric

vibrators generate when ~~receiving echoes of the ultrasonic wave,~~
the piezoelectric vibrators receive echoes of the ultrasonic wave,
which is generated by the piezoelectric vibrator to pass through
the acoustic propagation medium 16 made of solid or liquid and to
5 be reflected ~~on~~ in an inspection object made of a layer with a planar
or curved boundary and with a single acoustic characteristic or a
plurality of different acoustic characteristics, ~~via an acoustic~~
~~medium made of solid or liquid.~~

[0046] The amplifying circuits 5a, 5b-5i amplify the led electrical
10 signals to supply them to the A/D converters 6a, 6b to 6i. The A/D
converters 6a, 6b-6i A/D-convert the led electrical signals to lead
them to the parallel processor 7 in the signal processing part 8.

[0047] The parallel processor 7 in the signal processing part 8
processes the digital signals led from the A/D converters 6a, 6b-6i
15 to generate imaging data I, that is, to visualize a state of the
inspection object. Three-dimensional imaging data are generated
by aperture synthesizing from the electrical signals detected by
the signal detecting circuit 4, in correspondence to meshes in the
three-dimensional imaging area set in the inspection object. The
20 imaging data I generated by the parallel processor 7 are outputted
to the display processing device 10 and are subjected to
visualization/display processing there, and thereafter are
displayed on the display part 35.

[0048] The display processing device 10 has a two-dimensional image
25 generating part 31, an abnormality judging part 32, an outline drawing
part 33, an image connecting part 34, the display part 35, and so

on.

[0049] The two-dimensional image generating part 31 sees through the three-dimensional imaging data I from totally three directions, namely, a direction from a front face (X-Y plane) as viewed from the ultrasonic transducer, and directions vertical to two side faces (Y-Z plane), (Z-X plane) ~~straight~~ perpendicular to the front face, and in addition, it projects, on a two-dimensional plane, data with the largest value out of the imaging data stacked in the see-through directions out of the three-dimensional imaging data I in the respective directions to generate three two-dimensional images in the respective directions.

[0050] The abnormality judging part 32 compares values of the three-dimensional imaging data I corresponding to the respective meshes in the three-dimensional imaging area 40 with a judgment threshold value T (see Fig. 3) that is preset in a memory or the like to output meshes whose values are equal to or larger than the threshold value T and to automatically calculate a ratio that the number of the outputted meshes whose values are equal to or larger than the threshold value T makes up in the 3D imaging area 40, and determines that abnormality exists when the automatically calculated value is equal to or larger than a prescribed value.

[0051] The outline drawing part 33 draws the outline of the shape of the inspection object so as to overlay the outline on the three two-dimensional images generated by the two-dimensional image generating part 31.

[0052] The image connecting part 34 connects the plural imaging

data that are detected each time the relative position of the matrix sensor 9 and the inspection object is changed by the driving part 73 (see Fig. 6) being a mechanism part. Incidentally, the aforesaid abnormality judging part 32 outputs the meshes whose values are equal to or larger than the threshold value T based on the comparison with the judgment threshold value T (see Fig. 3) that is preset in the memory or the like for the two-dimensional images formed by the aforesaid two-dimensional image generating part 31 and for the connected images generated by the aforesaid image connecting part 34, and automatically calculates the ratio of the number of the outputted meshes whose values are equal to or larger than the threshold value T, and judges that the abnormality exists when the obtained value is equal to or larger than the prescribed value.

[0053] The display part 35 displays the imaging data and/or the judgment result inputted from each part, and it displays, for example, the imaging data inputted from the image connecting part 34 and/or the judgment result of the abnormality judging part 32. The display part 35 and the abnormality judging part 32 will be referred to as an abnormality judging/displaying part.

[0054] Specifically, the display processing device 10 has a function of changing brightness or transparency ~~of~~ with which respective meshes set in the three-dimensional area, according to values of the three-dimensional imaging data I generated by the signal processing part 8, ~~that the respective meshes have for the~~ ~~three-dimensional imaging data~~. The display processing device 10 also has a function of applying masking or image brightness correction

to an image of an unnecessary portion of the three-dimensional imaging data by multiplying the value of the three-dimensional imaging data I generated by the signal processing part 8 by a value that is set according to a three-dimensional coordinate position (Z, Y, Z).

5 **[0055]** The contents of processing where the display processing device 10 displays the aforesaid three-dimensional imaging data I outputted from the signal processing part 8 will be described with reference to Fig. 2A and Fig. 2B. Fig. 2A is a view showing the result of the 3D imaging of the inspection object 17 and Fig. 2B is a chart showing distribution R of reflection intensity of a surface-reflected wave in the 3D imaging area 40 in Fig. 2A.

10 **[0056]** As shown in Fig. 2A, the three-dimensional imaging data I is an aggregate of imaging data (i)51, imaging data (i + 1)52, imaging data (i + 2)53, imaging data (i + 3)54, imaging data (i + 4)55..., and so on which present the reflection intensity of the ultrasonic wave and are stored in correspondence to an imaging cell (i)41, an imaging cell (i + 1)42, an imaging cell (i + 2)43, an imaging cell (i + 3)44, an imaging cell (i + 4)45, ... and so on three-dimensionally arranged in the 3D imaging area 40.

20 **[0057]** Meanwhile, as for the distribution R of the reflection intensity of the surface-reflected wave, since the ultrasonic wave U is reflected on a surface S (depth Z = 0) in the inspection object 17, the reflection intensity in the 3D imaging area 40 becomes higher in the vicinity of the surface, as shown in Fig. 2B, to block an internal image. Therefore, respective values shown by the calibration curve C are added to the imaging data (i)51, imaging

25

data (i + 1)52, imaging data \pm (i + 2)53, imaging data (i + 3)54,
imaging data (i + 4)55, ... and so on according to a depth Z to make
the reflection intensity in the vicinity of the surface position
S small (transparent), whereby it is possible to make image brightness
5 in the vicinity of the surface and brightness of a deep portion uniform.
Note that the reference symbol G represents a gain.

[0058] Here, an imaging method where the 3D imaging area 40 is
seen through in the X, Y, and Z directions for displaying the visualized
information in the three-dimensional ultrasonographic device will
10 be described with reference to ~~Figs. 2~~ Fig. 2A to Fig. 2C. Out of
the imaging data (i)51, the imaging data (i + 1)52, the imaging data
(i + 2)53, the imaging data (i + 3)54, the imaging data (i + 4)55,
... arranged in line in the Z direction as shown in Fig. 2A, the
two-dimensional image generating part 31 selects the imaging data
15 with the maximum reflection intensity in the two-dimensional image
X-Y 60, namely, imaging data (imax) 57, as shown in, for example,
Fig. 2C, to output it to the outline drawing part 33 and the display
part 35.

[0059] Incidentally, in this example, the two-dimensional image
20 X-Y 60 which is the perspective image from the Z direction is described,
but as for perspective images in the X and Y directions, the
two-dimensional image generating part 31 selects the image data with
the maximum reflection intensity in the same manner as with the
perspective image from the Z direction to output them to the display
25 part 35.

[0060] ~~Figs. 3~~ Fig. 3A to Fig. 3C are views to illustrate the

processing performed in the display processing device 10 for automatically judging an abnormal portion 59 based on the inputted three-dimensional imaging data I. Note that in the drawings, the imaging data I in the 3D imaging area 40 present the reflection intensity of the ultrasonic wave.

[0061] When the three-dimensional imaging data I are inputted to the display processing device 10, similarly to the case in ~~Fig. 2~~ Fig. 2A to Fig. 2C, out of the imaging data (i)51, the imaging data (i + 1)52, the imaging data (i + 2)53, the imaging data (i + 3)54, the imaging data (i + 4)55, ... arranged in line in the Z direction as shown in Fig. 3A, the two-dimensional image generating part 31 selects the imaging data with the maximum reflection intensity in the two-dimensional image X-Y 60, namely, imaging data (imax) 57 as shown in Fig. 3B to output it to the outline drawing part 33 and the abnormality judging part 32. Incidentally, as for perspective images in the X and Y directions, the two-dimensional image generating part 31 selects the image data with the maximum reflection intensity in the same manner as with the perspective image from the Z direction to output them.

[0062] In order to make judgment regarding the abnormal portion 59, the abnormality judging part 32 selects (extracts) the imaging data I whose reflection intensity is equal to or larger than a judgment value A based on the judgment threshold value T preset in the memory or the like, and outputs it to the display part 35 for display, and it also calculates a ratio that the abnormal portion 59 makes up in the 3D imaging area 40 based on the result of counting the number

of the selected imaging data to judge whether or not the quality of the inspection object 17 is good.

[0063] Incidentally, the aforesaid abnormality judging part 32 outputs the meshes whose values are equal to or larger than the threshold value T, based on the comparison with the judgment threshold value T (see Fig. 3C) that is preset in the memory or the like for the two-dimensional images formed by the aforesaid two-dimensional image generating part 31 and for the connected images generated by the aforesaid image connecting part 34, and automatically calculates the ratio that the number of the outputted meshes whose values are equal to or larger than the threshold value T makes up in the 3D imaging area 40, and when the calculated value is equal to or larger than the prescribed value, it judges that the abnormality exists. In the drawing, the reference symbol T represents the threshold value, the reference symbol Z represents the depth, and the reference symbol A represents the judgment value.

[0064] The outline drawing part 33 draws a surface shape 61 of the inspection object 17, namely, its outline, on the two-dimensional image X-Y 60 inputted from the two-dimensional image generating part 31. This facilitates determining the position thereof relative to the defect image 58 in the inspection object 17.

[0065] An automating method for the abnormal judgment in which the abnormality judging part 32 judges whether or not the abnormality exists based on the two-dimensional imaging result generated by the two-dimensional image generating part 31 of the three-dimensional ultrasonographic device will be described with reference to [Figs.

4]] Fig. 4A to Fig. 4C.

[0066] In the two-dimensional image generating part 31, the three-dimensional imaging data (imax) 57, shown in Fig. 4B, in the abnormal portion 59 in the aforesaid two-dimensional image X-Y 60 which is a perspective image from the Z direction is the imaging data (i + 3) with the maximum reflection intensity which is extracted from the imaging data (i), the imaging data (i + 1), the imaging data (i + 2), the imaging data (i + 3), ... arranged in the Z direction in the 3D imaging area 40 shown in Fig. 4A, and therefore, when this imaging data (i + 3) is inputted to the abnormality judging part 32, the abnormality judging part 32 determines three-dimensional coordinates of the imaging data (i + 3). The abnormality judging part 32 also determines three-dimensional coordinates of the other imaging data of the abnormal portion 59 in the aforesaid two-dimensional image X-Y 60 in the similar manner. The same processing is executed for the perspective images in the X and Y directions.

[0067] Then, the abnormality judging part 32 compares post-processing three-dimensional shape information 101 and outline three-dimensional shape information 102 as shown in Fig. 4C which are set in the memory in correspondence to the three-dimensional imaging area 40, with the three-dimensional coordinates of the abnormal portion 59 in the aforesaid two-dimensional image X-Y 60, thereby three-dimensionally judging an interference portion 105 where the interference with a post-processed portion exists.

[0068] Further, when making the judgment, the abnormality judging

part 32 automatically calculates the area of the abnormal portion based on the judgment on the adjacency state of the determined three-dimensional coordinates of all the imaging data of the abnormal portion 59, namely, based on the judgment on whether or not the imaging data of the abnormal portion 59 are adjacent to the post-processing three-dimensional shape information 101 and the outline three-dimensional shape information 102, and judges whether or not the automatically calculated area of the abnormal portion is equal to or larger than the prescribed value, and based on this judgment result, it judges whether or not the abnormal portion 59 is a defect that cannot be neglected.

[0069] The abnormality judging part 32 outputs the aforesaid judgment result to the display part 35, and the display part 35 displays the inputted judgment result.

[0070] Further, as shown in Fig. 5A, the abnormality judging part 32 selects the maximum reflection intensity in the Z direction (as well as in the X and Y directions) shown in Fig. 4B directly from the three-dimensional imaging result of the three-dimensional ultrasonographic device, and compares the post-processing three-dimensional shape information 101 and the outline three-dimensional shape information 102 as shown in Fig. 5B, which are set in the memory in correspondence to the three-dimensional imaging area 40, with the three-dimensional coordinates of the abnormal portion 59 in the aforesaid two-dimensional image X-Y 60, thereby three-dimensionally judging the interference portion 105 between the post-processed portion and the abnormal portion 59.

[0071] Further, when making the judgment, the abnormality judging part 32 discriminates the adjacency state of the determined three-dimensional coordinates of all the imaging data of the abnormal portion 59 to automatically calculate the area of the abnormal portion, and it also judges whether or not the automatically calculated area of the abnormal portion is ~~abnormally~~ equal to or larger than the prescribed value, and based on this judgment result, it judges whether or not the abnormal portion is a defect that cannot be neglected. The abnormality judging part 32 outputs the judgment result to the display part 35, and the display part 35 displays the inputted judgment result.

[0072] Fig. 6 is a view to illustrate the image connection processing when the interior of an inspection object 81 larger than a detection area of the matrix sensor 9 (larger than the matrix sensor 9) is imaged. Here, the inspection of the inspection object 81 in a solid cylindrical shape will be described as an example. A driving part 73 mechanically drives the inspection object 81 (or may mechanically drive the matrix sensor 9), and has a sensor detecting the movement position thereof. In this case, the inspection object 81 (or the matrix sensor 9) is driven by the driving part 73 to rotate in the arrow direction.

[0073] Meanwhile, the image connecting part 34 of the display processing device 10 connects the plural imaging data that are detected by the sensor every time the relative position of the inspection object 81 and the matrix sensor 9 is changed by the driving part 73, and rearranges and outputs the image data.

[0074] The image data obtained when the inspection object 81 is rotated four times by, for example, 90° at each rotation by the driving part 73 are connected by the image connecting part 34 and are rearranged to be outputted to the display part 35, so that the imaging results of the whole inspection object ~~74~~ 81 can be collectively displayed on a display screen 80 as shown in Fig. 7, so that it is possible to obtain the display screen 80 where the position of a defect 72 in the inspection object ~~74~~ 81 is easily recognized from a defect image 79 spreading across the plural ~~screens~~ images. Note that an image (1) 75, an image (2) 76, an image (3) 77, and an image (4) 78 are displayed in correspondence to the angles of 90 degrees, 180 degrees, 270 degrees, and 360 degrees.

[0075] Incidentally, the abnormality judging part 32 is capable of outputting meshes whose values are equal to or larger than a threshold value T based on the comparison with the judgment threshold value T (see Fig. 3) which is preset in a memory or the like for the connected images generated by the aforesaid image connecting part 34, and automatically calculating a ratio of the number of the outputted meshes whose values are equal to or larger than the threshold value T, and judging that abnormality exists when the calculated value is equal to or larger than a predetermined value.

[0076] Fig. 8 is an explanatory view showing a state where a masking part 94 is used to cover an inspection object 91 for imaging the interior thereof, in inspecting the inspection object 91 whose inspection area 82 is in a shape more protruding from the surrounding area. In the drawing, an ultrasonic wave path U1 represents imaging

without any masking part 94, and in this case, a drawn image U1 (which becomes a spheroid on a curved surface whose distances from a transmission piezoelectric vibrator 21a and a transmission piezoelectric vibrator 22a are equal) overlaps the interior of the inspection object 91.

[0077] Therefore, in this case, the masking part 81 having an aperture at the position corresponding to the inspection area 82 is put over the inspection object 91 to partly cover the surface of the inspection object 91.

[0078] A drawn image U2 by an ultrasonic wave path U2 when the surface of the inspection object 91 is covered with such a masking part 94 does not overlap the interior of the inspection object 91, which makes it possible to eliminate a problem that the ultrasonic wave is reflected due to the influence of an uneven portion of the periphery to deteriorate image quality of the internal image of the inspection object when the interior of the inspection object 91 is imaged.

[0079] Thus, according to the three-dimensional ultrasonographic device of this embodiment, quantitative inspection is enabled by directly judging values of brightness display and of the imaging data corresponding to the values of the three-dimensional imaging data synthesized from numeral reflected echoes from the interior of the inspection object, the reflected echoes being obtained by the ultrasonic wave transmission/reception by the matrix sensor 9 composed of the plural piezoelectric vibrators independently formed in a matrix.

[0080] Further, the values of the imaging data are amplified according to the depth of the three-dimensional imaging area, which enables the correction of the influence of the surface-reflected wave of the inspection object and the correction of the attenuation of the ultrasonic wave in the inspection object. Moreover, the driving part 73 capable of moving the matrix sensor 9 while detecting the position thereof is provided and the plural imaging data are connected according to the position of the matrix sensor 9, which enables imaging of a wider area.

[0081] Furthermore, the masking part 94 having the aperture at the position corresponding to the inspection area on the surface of the inspection object is provided so as to cover the surface of the inspection object, which makes it possible to prevent the image quality of the internal image from deteriorating due to the ultrasonic wave reflected on the uneven portion in the periphery of the inspection area.

[0082] Furthermore, the values of the imaging data are amplified according to the depth of the three-dimensional imaging area, which enables the correction of the influence of the surface-reflected wave of the inspection object and the correction of the attenuation of the ultrasonic wave in the inspection object.

[0083] Moreover, automatic judgment of the inspection becomes possible since the abnormality judging part 32 and the display part 35 are provided, these parts comparing the values of the three-dimensional imaging data corresponding to the meshes in the area of the two-dimensional images generated by the two-dimensional

image generating part 31, with the set value preset in the memory,
and finding the meshes whose values are equal to or larger than the
set value, to compare the three-dimensional coordinates of the found
imaging meshes with the three-dimensional shape information on the
5 outline shape of the inspection object and on the post-processed
portion, which are preset in the memory, thereby detecting the
existence or not of the interference between the defect position
and the post-processed portion in the inspection object to display
the result thereof.

10 **[0084]** As a result, it is possible to provide a three-dimensional
ultrasonographic device achieving improved accuracy of internal
inspection using the ultrasonic wave, a wider inspection area, and
automatic judgment of the inspection.

[0085] It should be noted that the present invention is not limited
15 to the above-described embodiment.

[0086] In the above-described embodiment, the three-dimensional
imaging device includes the signal processing part 8 and the display
processing device 10, but they may be realized by independent
computers respectively.

20 **[0087]** The computers execute each processing in this embodiment
based on programs stored in a storage medium, and may take any structure,
for example, may take a form of a single device such as a personal
computer, a system in which a plurality of devices are connected
via a network, or the like. Further, the computer is not limited
25 to a personal computer (PC), but includes a processor, a microcomputer,
and the like included in communication equipment or information

processing equipment, and represents all the equipment and devices capable of realizing the functions of the present invention by programs.

[0088] The internal structure of the display processing device
5 10 in the above-described embodiment is realizable by software. The software may be stored in a computer-readable storage medium such as a flexible disk, or may be transmitted on a network such as LAN or the Internet as single software (program). In this case, the computer reads the software (program) stored in the storage medium
10 or the computer downloads the software (program) from a site (server) on LAN or the Internet to install it on a hard disk, so that the processing in the computer becomes possible. In short, the software (program) in the present invention is not limited to that stored in the storage medium independent from the computer, but includes
15 that distributed via a transmission medium such as LAN or the Internet.

[0089] Incidentally, a language format and a storage format of the program may be any as long as the program is stored in a storage medium such as a memory, a flexible disk, a hard disk, an optical disk (CD-ROM, CD-R, DVD, or the like), a magneto-optic disk (MO or
20 the like), and a semiconductor memory so as to be computer readable.

[0090] Furthermore, each processing for realizing this embodiment may be partly executed by MW (middleware) running on a computer, such as OS (operating system), database management software, or network software, based on an instruction of a program installed
25 in the computer from the storage medium. Further, the storage medium is not limited to a medium independent from the computer, but also

includes a storage medium storing or temporarily storing a program transmitted and downloaded via LAN or the Internet. Moreover, the number of the storage media is not limited to one, but a case where the processing in this embodiment is executed from a plurality of
5 media is also embraced in the present invention, and the structure of the storage medium may be any.

Industrial Applicability

[0091] The present invention is applicable to the work of
10 inspecting the interior of an inspection object by ultrasonic waves.